

CEMENT REMOVER

STRONG ACID COMPOUND USED FOR REMOVING CEMENT RESIDUES FROM MOST COMMON METAL SURFACES. IT MUST NOT BE USED ON ZINC, ALUMINIUM, GALVANISED MATERIALS AND STAINLESS STEEL

FEATURES & BENEFITS:

- Fast and efficient cement removal
- Non-caustic / non-phosphate
- Water-based
- Non-toxic
- Non-solvent, non-butyl
- Safe on paint, glass, plastics and most metals
- Strong and effective removal of cement and concrete splatter on cargo holds, machinery and equipment
- Cost-effective and easy to use
- Inhibited against attack on ferrous metals
- Non-flammable
- Safe to use on most tank surfaces and most coatings

DIRECTIONS FOR USE:

Apply CEMENT REMOVER with a brush to surfaces to be cleaned.

In general, 2-5% dilution with water is an ideal dosage to clean cargo holds without affecting the coatings. Use undiluted for hard cement deposits on the surfaces. Use diluted in solution of 25-50%, depending on the thickness of the cement layer. Rinse thoroughly with water after 10-15 minutes after application.

STANDARD PACKING:

CEMENT REMOVER is usually available in plastic cans of 25 L and plastic drums of 200 L.