



CHLOR 12

BACTERICIDE DISINFECTANT FOR POTABLE WATER,
STORAGE TANKS AND LINES

DESCRIPTION:

Sodium hypochlorite liquid at 12% compliant UNI EN 901-2013.

APPLICATIONS:

To disinfect potable water in aqueducts, water storage systems and sewage tanks.

ADVANTAGES:

CHLOR 12 controls and eliminates bacteria, maintaining water potable. Sodium hypochlorite at 12% is universally recognized as disinfectant of potable water by Health Departments and its use is approved for municipal water systems.

INSTRUCTIONS:

In the point as far as possible from the potable water tank (Example highest deck – bridge), residual active chlorine must be maintained at a minimum level of 0.2 ppm. In the potable water tanks, maintain residue chlorine level between 0.5 and 2 ppm, which will guarantee an adequate antibacterial protection. To obtain 2 PPM in a potable water tank, add 2 mg of CHLOR 12 each liter of water. CHLOR 12 may be added manually or automatically at the water inlet point through a metering system connected with an impulse water meter (see bulletin U/4).

Please contact our technical service for any further information.

To control the correct level of Chlorine in the water use SHERAN CHEMICALS CHLORINE TEST KIT with DPD1 Tablets (see bulletin T/3).

PRECAUTIONS:

Alkaline product: do not swallow or inhale, avoid prolonged contact with eyes or skin. Use rubber gloves and protective glasses. In case of contact with eyes or skin, rinse thoroughly with fresh running water for at least 20 minutes.

PACKAGING:

Plastic pails 25 L.